



Fig. Safe AWS1500, hinge right E-Lock M-Locks EM3520, 3 shelves





EN1143-1 Burglary Protection



Grade I



Grade I



Class EN 1



Class I E



4102 (light fire protection)



Domestic insurable up to EUR 65.000



Commercial insurable up to EUR 20.000

[Safes] [Type AWS]

AWS series safes offer a roomy interior with relatively low transportation weight. An internal width of 740 mm provides sufficient space to accommodate up to 9 file folders. All models are pre-fitted to enable connection to a burglar alarm system.

[Product information]

Hinge DIN right – model designation R

option: DIN left

Door opening angle 180°

Body double-walled, filled with high resistant barrier material

Door structure triple-walled, filled with high resistant barrier material, internal boltwork

protected by sheets of hardened steel to give extra anti-drill resistance

Locking mechanism three-way moving boltwork with large steel bolts protected by additional emer-

gency re-lockers, continuous fixed full height bolt on the hinge side

Anchoring prepared for floor and rear wall anchoring

anchoring bolts and shields are supplied

option: additional anchoring holes (customer specifies position)

Alarm connection VdS-certified cable channels to allow connection to a burglar alarm system

Colour inside and outside RAL 7037 dusty grey

option: special colour according to RAL

Lock model designation K – double-bit lock VdS class 1, Cawi 2 keys (95 mm)

model designation E — electronic lock VdS class 2, M-Locks EM3520 option: other lock models (primary lock or possible secondary locks)

Equipment shelf adjustable (height setting 60 mm, AWS1500 90 mm)

option: additional shelf, inside locker

Accessories option: certified steel plinth to raise the level of the safe,


fire protection door rebate seals, alarm switch set,

interior lighting

SH Model Outside dimensions Inside dimensions Volume Weight hxwxd(mm) (I) (appr. kg) h x w x d (mm)AWS0800RK / AWS0800RE 770 x 790 x 650 720 x 740 x 525 1 280 310 AWS1000RK / AWS1000RE 950 x 790 x 650 900 x 740 x 525 2 350 360 AWS1200RK / AWS1200RE 1130 x 790 x 650 1080 x 740 x 525 2 420 410 AWS1500RK / AWS1500RE 1490 x 790 x 650 1440 x 740 x 525 3 559 510

[Equipment options]





AWS1000

