



Fig. Safe BG20, hinge right K-Lock Cawi 2 keys (95 mm), 1 lockable drawer, 1 drawer, 1 shelf

DESIGNED IN AUSTRIA

MADE IN EUROPE



EN1143-1 Burglary Protection



Grade II



Grade II



Class EN 2



Class II E



4102 (light fire protection)



Domestic insurable up to EUR 100.000



Commercial insurable up to EUR 50.000

[Safes] [Type BG]

BG series safes are designed for narrow spaces. They provide space to accommodate up to 5 file folders and the option of additional locks to give dual control.

Armoured, high resistant barrier material ensures a grade II classification.

[Product information]

Hinge DIN right – model designation R

option: DIN left

Door opening angle 180°

Body double-walled, filled with armoured, high resistant barrier material

Door structure triple-walled, filled with armoured, high resistant barrier material,

internal boltwork protected by sheets of hardened steel

to give extra anti-drill resistance

Locking mechanism three-way moving boltwork with large steel bolts protected by additional emer-

gency re-lockers, continuous fixed full height bolt on the hinge side

Anchoring prepared for floor and rear wall anchoring

anchoring bolts and shields are supplied

option: additional anchoring holes (customer specifies position)

Alarm connection VdS-certified cable channels to allow connection to a burglar alarm system

(from BG15 up)

Colour inside and outside RAL 7037 dusty grey

option: special colour according to RAL

Lock model designation K – double-bit lock VdS class 1, Cawi 2 keys (95 mm)

model designation E — electronic lock VdS class 2, M-Locks EM3520 option: other lock models (primary lock or possible secondary locks)

Equipment shelf adjustable (height setting 85 mm)

option: additional shelf, inside locker, drawer, pull-out shelf

Accessories option: certified steel plinth to raise the level of the safe,

fire protection door rebate seals,

alarm switch set (from BG15 up), interior lighting

Model	Outside dimensions	Inside dimensions	SH	Volume	Weight
_	h x w x d (mm)	h x w x d (mm)		(1)	(appr. kg)
BG10RK / BG10RE	395 x 450 x 442	345 x 400 x 310	1	43	120
BG15RK / BG15RE	565 x 450 x 442	515 x 400 x 310	1	64	150
BG20RK / BG20RE	735 x 450 x 442	685 x 400 x 310	1	85	180
BG25RK / BG25RE	905 x 450 x 442	855 x 400 x 310	2	106	215
BG30RK / BG30RE	1075 x 450 x 442	1025 x 400 x 310	2	127	245
BG35RK / BG35RE	1245 x 450 x 442	1195 x 400 x 310	3	148	280
BG40RK / BG40RE	1415 x 450 x 442	1365 x 400 x 310	3	169	310

