



Fig. Safe BP15, hinge right E-Lock M-Locks 3520, 1 shelf





EN1143-1 Burglary protection



EN15659 Fire protection



Grade II



Grade II + LFS30 (BP10/41 - LFS60)



Class EN 2



Class II E



Domestic insurable up to EUR 100.000



Commercial insurable up to EUR 50.000

[ Safes ] [ Type BP ]

In addition to the qualities of the BM safes, the BP series safes offer certified protection against fire. Additional heat absorbent materials and fire and smoke protection seals in the door rebates provide fire protection – tested and certified in grade LFS30 (BP10/41 – LFS60).

## [ Product information ]

Hinge DIN right – model designation R

option: DIN left

Door opening angle 180°

Body double-walled, filled with armoured, high resistant barrier and heat absorbent

materials

Door structure triple-walled with double rebate, filled with armoured, high resistant barrier

material and heat absorbent materials, internal boltwork protected by sheets of hardened steel to give extra anti-drill resistance, door rebate fitted with several

fire and smoke protection seals

Locking mechanism three-way moving boltwork with large steel bolts protected by additional emer-

gency re-lockers, continuous fixed full height bolt on the hinge side

Anchoring prepared for floor and rear wall anchoring

anchoring bolts and shields are supplied

Alarm connection VdS-certified cable channels to allow connection to a burglar alarm system

Colour inside and outside RAL 7037 dusty grey

option: special colour according to RAL

Lock model designation K – double-bit lock VdS class 1, Cawi 2 keys (145 mm)

model designation E — electronic lock VdS class 2, M-Locks EM3520 option: other lock models (primary lock or possible secondary locks)

Equipment shelf adjustable (height setting 85 mm)

option: additional shelf, inside locker, drawer, pull-out shelf

Accessories option: alarm switch set, interior lighting

Model	Outside dimensions	Inside dimensions	SH	Volume	Weight
	h x w x d (mm)	h x w x d (mm)		(1)	(appr. kg)
BP10RK / BP10RE *	474 x 605 x 522	360 x 495 x 310	1	55	190
BP15RK / BP15RE	629 x 605 x 522	515 x 495 x 310	1	79	235
BP20RK / BP20RE	799 x 605 x 522	685 x 495 x 310	1	105	280
BP25RK / BP25RE	969 x 605 x 522	855 x 495 x 310	2	131	325
BP30RK / BP30RE	1139 x 605 x 522	1025 x 495 x 310	2	157	375
BP35RK / BP35RE	1309 x 605 x 522	1195 x 495 x 310	3	183	420
BP40RK / BP40RE	1479 x 605 x 522	1365 x 495 x 310	3	209	465
BP41RK / BP41RE *	1479 x 765 x 582	1365 x 655 x 370	3	331	580

