



Fig. Safe BWS1000, hinge right K-Lock Cawi 2 keys (95 mm), 2 shelves





EN1143-1 Burglary protection



Grade II



Grade II



Class EN 2



Class II E



4102 (light fire protection)



Domestic insurable up to EUR 100.000



Commercial insurable up to EUR 50.000

[Safes] [Type BWS]

BWS series safes offer a roomy interior with relatively low transportation weight. All models are prefitted to enable connection to a burglar alarm system. Armoured, high resistant barrier material ensures a grade II classification.

[Product information]

Hinge DIN right – model designation R

option: DIN left

Door opening angle 180°

Body double-walled, filled with armoured, high resistant barrier material triple-walled, filled with armoured, high resistant barrier material,

internal boltwork protected by sheets of hardened steel

to give extra anti-drill resistance

Locking mechanism three-way moving boltwork with large steel bolts protected by additional emer-

gency re-lockers, continuous fixed full height bolt on the hinge side

Anchoring prepared for floor and rear wall anchoring

anchoring bolts and shields are supplied

option: additional anchoring holes (customer specifies position)

Alarm connection VdS-certified cable channels to allow connection to a burglar alarm system

Colour inside and outside RAL 7037 dusty grey

option: special colour according to RAL

Lock model designation K – double-bit lock VdS class 1, Cawi 2 keys (95 mm)

model designation E – electronic lock VdS class 2, M-Locks EM3520 option: other lock models (primary lock or possible secondary locks)

Equipment shelf adjustable (height setting 60 mm, BWS1500 90 mm)

option: additional shelf, inside locker

Accessories option: certified steel plinth to raise the level of the safe,


fire protection door rebate seals, alarm switch set,

interior lighting

	Model	Outside dimensions	Inside dimensions	SH	Volume	Weight
		h x w x d (mm)	h x w x d (mm)		(I)	(appr. kg)
	BWS0800RK / BWS0800RE	770 x 790 x 650	720 x 740 x 525	1	280	340
	BWS1000RK / BWS1000RE	950 x 790 x 650	900 x 740 x 525	2	350	395
	BWS1200RK / BWS1200RE	1130 x 790 x 650	1080 x 740 x 525	2	420	450
	BWS1500RK / BWS1500RE	1490 x 790 x 650	1440 x 740 x 525	3	559	560

[Equipment options]









BWS1500

Please add 60 mm to the listed outside depth for mountings.