



Fig. Safe CP25, hinge right E-Lock M-Locks EM3520, 2 shelves





EN1143-1 Burglary protection



EN15659 Fire protection



Grade III



Grade III + LFS30



lass FN 3



Class III E



Domestic insurable up to EUR 200.000



Commercial insurable up to EUR 100.000

[Safes]

s] [Type CP]

In addition to the qualities of the CM safes, the CP series safes also offer certified protection against fire. Additional heat absorbent materials and fire and smoke protection seals in the door rebates provide fire protection – tested and certified in grade LFS30.

[Product information]

Hinge DIN right – model designation R

option: DIN left

Door opening angle 180°

Body double-walled, reinforced, filled with armoured, high resistant barrier and

heat absorbent materials

Door structure triple-walled with double rebate, reinforced, filled with armoured,

high resistant barrier material and heat absorbent materials, internal boltwork protected by sheets of hardened steel to give extra anti-drill resistance,

door rebate fitted with several fire and smoke protection seals

Locking mechanism boltwork with large steel bolts,

protected by additional emergency re-lockers,

continuous fixed full height bolt on the hinge side

Anchoring prepared for floor and rear wall anchoring

anchoring bolts and shields are supplied

Alarm connection VdS-certified cable channels to allow connection to a burglar alarm system

Colour inside and outside RAL 7037 dusty grey

option: special colour according to RAL

Lock model designation K – double-bit lock VdS class 2, S+G 2 keys (140 mm)

model designation E – electronic lock VdS class 2, M-Locks EM3520 option: other lock models (primary lock or possible secondary locks)

Equipment shelf adjustable (height setting 85 mm)

option: additional shelf, inside locker, drawer, pull-out shelf


Accessories option: alarm switch set, interior lighting


Model	Outside dimensions	Inside dimensions	SH	Volume	Weight
	h x w x d (mm)	h x w x d (mm)		(1)	(appr. kg)
CP15RK / CP15RE	629 x 605 x 522	515 x 495 x 310	1	79	295
CP20RK / CP20RE	799 x 605 x 522	685 x 495 x 310	1	105	350
CP25RK / CP25RE	969 x 605 x 522	855 x 495 x 310	2	131	410
CP30RK / CP30RE	1139 x 605 x 522	1025 x 495 x 310	2	157	465
CP35RK / CP35RE	1309 x 605 x 522	1195 x 495 x 310	3	183	520
CP40RK / CP40RE	1479 x 605 x 522	1365 x 495 x 310	3	209	575











CP15 CP20 CP25 CP30 CP35 CP40