



up to EUR 150.000

Fig. Safe DWS0850, hinge right E-Lock Kaba Paxos advance Set 1 (keypad) + Set 5, 1 shelf

Model	Outside dimensions	Inside dimensions	SH	Volume	Weight
	h x w x d (mm)	h x w x d (mm)		(I)	(appr. kg)
DWS0849R	848 x 645 x 565	695 x 495 x 320	1	110	635
DWS0850R	848 x 810 x 725	695 x 660 x 480	1	220	875
DWS1000R	1003 x 810 x 725	850 x 660 x 480	2	269	1030
DWS1200R	1193 x 810 x 725	1040 x 660 x 480	2	329	1150
DWS1600R	1538 x 810 x 725	1385 x 660 x 480	3	439	1405
DWS1901R	1883 x 810 x 725	1730 x 660 x 480	4	548	1680
DWS1903R	1883 x 1110 x 725	1730 x 960 x 480	4	797	2090
DWS1902	1883 x 1110 x 725	1730 x 960 x 480	4	797	2130
DWS1904	1883 x 1415 x 725	1730 x 1265 x 480	4	1050	2550

[Safes]

[Type DWS]

A distinctive feature of the DWS series safes is their solid construction plus their size (DWS 1902 and DWS1904 double-doored) and they are available with optional fire protection – tested and certified in grade LFS60. Safes weighing less than 1.000 kg must be anchored.

[Product information]				
Hinge	DIN right – model designation R (DWS1902, DWS1904 double-doored) option: DIN left			
Door opening angle 180°				
Body	double-walled, reinforced, filled with armoured, high resistant barrier material			
Door structure	triple-walled, reinforced, filled with armoured, high resistant barrier material, internal boltwork protected by sheets of hardened steel to give extra anti-drill resistance			
Locking mechanisn	n three-way moving boltwork with large steel bolts, protected by glass plate with additional emergency re-lockers, fix engaging steel bolts on the hinge side			
Anchoring	fitted for floor anchoring anchoring bolts and shields are supplied for DWS0849, DWS0850 option: additional anchoring holes (customer specifies position)			
Alarm connection	VdS-certified cable channels to allow connection to a burglar alarm system			
Colour	inside and outside RAL 7037 dusty grey option: special colour according to RAL			
Lock	safes in grades IV and higher have to be equipped with at least 2 certified locks any set of locks (from VdS class 2 up) is possible			
Equipment	shelf adjustable (height setting 69 mm, DWS0849 60 mm) option: additional shelf, inside locker option (from DWS0850 up): drawer, pull-out shelf			
Accessories	option: fire protection door rebate seals, alarm switch set, interior lighting			
Option	additional certified fire protection LFS60 – except models: DWS0849, DWS1902, DWS1904 bolted version from Model DWS1000 up – assembly on site			



Please add 60 mm to the listed outside depth for mountings.