



up to EUR 250.000

Fig. Safe EWS1000, hinge right

2 x K-Lock S+G adjustable each 1 key guide tube 2 bits, 2 shelves

| Model    | Outside dimensions | Inside dimensions | SH | Volume | Weight     |
|----------|--------------------|-------------------|----|--------|------------|
|          | h x w x d (mm)     | h x w x d (mm)    |    | (I)    | (appr. kg) |
| EWS0849R | 848 x 645 x 565    | 695 x 495 x 320   | 1  | 110    | 665        |
| EWS0850R | 848 x 810 x 725    | 695 x 660 x 480   | 1  | 220    | 935        |
| EWS1000R | 1003 x 810 x 725   | 850 x 660 x 480   | 2  | 269    | 1060       |
| EWS1200R | 1193 x 810 x 725   | 1040 x 660 x 480  | 2  | 329    | 1220       |
| EWS1600R | 1538 x 810 x 725   | 1385 x 660 x 480  | 3  | 439    | 1505       |
| EWS1901R | 1883 x 810 x 725   | 1730 x 660 x 480  | 4  | 548    | 1790       |
| EWS1903R | 1883 x 1110 x 725  | 1730 x 960 x 480  | 4  | 797    | 2230       |
| EWS1902  | 1883 x 1110 x 725  | 1730 x 960 x 480  | 4  | 797    | 2270       |
| EWS1904  | 1883 x 1415 x 725  | 1730 x 1265 x 480 | 4  | 1050   | 2720       |

Please add 60 mm to the listed outside depth for mountings.

## [Safes]

EWS series safes are designed for total protection and offer Wertheim's usual level of high security. They are available with optional fire protection – tested and certified according to LFS60. Safes weighing less than 1.000 kg must be anchored.

| [ Product | information ] |  |
|-----------|---------------|--|
|           |               |  |

| Hinge                   | DIN right – model designation R (EWS1902, EWS1904 double-doored)<br>option: DIN left  |  |  |  |
|-------------------------|---|--|--|--|
| Door opening angle 180° |   |  |  |  |
| Body                    | double-walled, reinforced, filled with armoured, high resistant barrier material  |  |  |  |
| Door structure          | triple-walled, reinforced, filled with armoured, high resistant barrier material,<br>internal boltwork protected by sheets of hardened steel<br>to give extra anti-drill resistance |  |  |  |
| Locking mechanisr       | n three-way moving boltwork with large steel bolts,<br>protected by glass plate with additional emergency re-lockers,<br>fix engaging steel bolts on the hinge side                 |  |  |  |
| Anchoring               | fitted for floor anchoring<br>anchoring bolts and shields are supplied for EWS0849, EWS0850<br>option: additional anchoring holes (customer specifies position)                     |  |  |  |
| Alarm connection        | VdS-certified cable channels to allow connection to a burglar alarm system  |  |  |  |
| Colour                  | inside and outside RAL 7037 dusty grey<br>option: special colour according to RAL   |  |  |  |
| Lock                    | safes in grades IV and higher have to be equipped with at least 2 certified locks<br>any set of locks (from VdS class 2 up) is possible   |  |  |  |
| Equipment               | shelf adjustable (height setting 69 mm, EWS0849 60 mm)<br>option: additional shelf, inside locker<br>option (from EWS0850 up): drawer, pull-out shelf                               |  |  |  |
| Accessories             | option: fire protection door rebate seals, alarm switch set, interior lighting  |  |  |  |
| Option                  | additional certified fire protection LFS60P – except models:<br>EWS0849, EWS1902, EWS1904<br>bolted version from Model EWS1000 up up – assembly on site                             |  |  |  |

