



Fig. Wall safe AMS0600, hinge right K-Lock Cawi 2 keys (95 mm), 1 shelf





EN1143-1 Burglary protection



Grade I





Class EN 1



4102 (light fire protection)



Domestic insurable up to EUR 65.000



Commercial insurable up to EUR 20.000

[Wall safes] [Type AMS]

AMS series wall safes are designed for installation into suitable masonry. They are set into the wall so that the front (the door) is aligned with the wall and the body is encased with a minimum of 10 cm of concrete. The optional rear wall armouring allows a wall thickness equivalent to the safe depth.

[Product information]

Hinge DIN right (internal) - model designation R

option: DIN left

Door opening angle 95°

Body hot galvanised steel plate construction to resist corrosion

triple-walled, massive steel design, internal boltwork protected by sheets of Door structure

hardened steel to give extra anti-drill resistance

Locking mechanism three-way moving boltwork with large steel bolts protected by additional emer-

gency re-lockers, continuous fixed full height bolt on the hinge side

inside and outside RAL 7037 dusty grey Colour

option: special colour according to RAL

Lock model designation K - double-bit lock VdS class 1, Cawi 2 keys (95 mm)

model designation E - electronic lock VdS class 2, M-locks EM3520 option: other lock models (primary lock or possible secondary lock)

shelf adjustable (height setting 80 mm) Equipment

option: additional shelf


option (only at models with outside depth 380 mm): inside locker

Accessories option: rear wall armor, interior lighting

models AMS0401, AMS0601, AMS0801, AMS1001 do not offer enough depth Note

for file folders DIN A4, one file folder can be stored behind the door

Model	Outside dimensions	Inside dimensions	SH	Volume	Weight
	h x w x d (mm)	h x w x d (mm)		(1)	(appr. kg)
AMS0400RK / AMS0400RE	410 x 510 x 380	360 x 460 x 295	1	49	50
AMS0401RK / AMS0401RE	410 x 510 x 230	360 x 460 x 145	1	24	45
AMS0600RK / AMS0600RE	590 x 510 x 380	540 x 460 x 295	1	73	65
AMS0601RK / AMS0601RE	590 x 510 x 230	540 x 460 x 145	1	36	60
AMS0800RK / AMS0800RE	770 x 510 x 380	720 x 460 x 295	1	98	80
AMS0801RK / AMS0801RE	770 x 510 x 230	720 x 460 x 145	1	48	70
AMS1000RK / AMS1000RE	950 x 510 x 380	900 x 460 x 295	2	122	95
AMS1001RK / AMS1001RE	950 x 510 x 230	900 x 460 x 145	2	60	85



AMS0600

[Equipment options]

