

Fig. Deposit safe AG15DF - front drawer, K-Lock Cawi 2 keys (95 mm), drawer lock: E-Lock M-Locks EM2020 swing bolt, option: 1 storage protection

Drop-in goods:  
 Envelopes, safe bags, bags  
 Length: 150-300 mm, width: 100-145 mm, thickness: 2-30 mm

Model	Outside dimensions h x w x d (mm)	Inside dimensions usable h x w x d (mm)	Volume usable (l)	Weight (appr. kg)
AG15DF - front drawer	565 x 450 x 442	215 x 400 x 310	27	155
AG20DF - front drawer	735 x 450 x 442	385 x 400 x 310	48	180
AG25DF - front drawer	905 x 450 x 442	555 x 400 x 310	69	210
AG30DF - front drawer	1075 x 450 x 442	725 x 400 x 310	90	235

### [ Deposit safes with drop-in drawer ]

### [ Type AGDF ]

Deposit safes with a certified drop-in drawer offers a simple and secure storage solution for business where daily receipts need to be deposited and protected from theft and robbery (e.g. gas stations, restaurants, retail chains). The drop-in drawer has been tested against the use of force and the removal of deposits.

- The drop-in goods are thrown in via the lockable drop-in drawer.
- Subsequent removal or „fishing“ is prevented by the anti-fishing plates.
- The deposited goods can only be removed from the collection cabinet by authorized persons.

### [ Product information - Collection cabinet ]





Hinge	DIN right
Door opening angle	180°
Body	double-walled, filled with high resistant barrier material
Door structure	triple-walled, filled with high resistant barrier material, internal boltwork protected by sheets of hardened steel to give extra anti-drill resistance
Locking mechanism	three-way moving boltwork with large steel bolts, protected by additional emergency re-lockers, continuous fixed full height bolt on the hinge side
Anchoring	prepared for 4-way floor fastening, anchoring material included: 4 x Hilti HST M16x140/25 (for mounting directly on concrete floors) option: 4 x Hilti HST M16x215/100 (for concrete floors with max. 80 mm floor structure to the load-bearing concrete)
Alarm connection	VdS-certified cable channels to allow connection to a burglar alarm system (EMA) (from Model AG20DF up)
Colour	inside and outside RAL 7037 dusty grey (option: special colour according to RAL)
Lock	double-bit lock VdS class 1, Cawi 2 keys (95 mm) or electronic lock VdS class 2, M-locks EM3520 option: other lock models (primary lock or possible secondary lock)
Equipment	option: shelf, inside locker (height 340 mm), retaining plate, lockable collection box
Accessories	option: fire protection door rebate seals, alarm switch set (from AG20DF up), interior lighting

### [ Product information - Slot drawer ]

Drawer structure	triple-walled, filled with high resistant barrier material, internal boltwork protected by sheets of hardened steel to give extra anti-drill resistance, solid steel construction with anti-fishing device
Locking mechanism	two-way moving boltwork with large steel bolts
Drawer dimensions	142,5 h x 450 w x 442 d(mm)
Drawer position	front (models DF) or rear (on request)
Colour	inside and outside RAL 7037 dusty grey (always identical to the collection cabinet colour)
Drawer lock	double-bit lock VdS class 1, Cawi 2 keys (95 mm) or electronic lock VdS class 2, M-locks EM2020 swing bolt option: other lock models
Equipment	option: drawer equipment with 4 banknote compartments and coin compartments and lockable cover (deposited values in the drawer equipment are not D-I / EN 1 insured - consultation with the insurer is required)



Fig. Deposit safe AM25, hinge right  
E-Lock M-Locks EM3520, without equipment, drop-in equipment LBE150 front and center



### [ Deposit safes with drop-in equipment ]

Safes with drop-in equipment offer a simple and secure depositing of e.g. daily cash receipts and are mainly used if more than one person deposit values (e.g. gas stations, restaurants, retail chains).

- Drop-in goods (e.g. zipp-bag) are deposited through the drop-in flap into the safe.
- A security anti-fishing device prevents the later removal of a deposited bag.
- The deposited goods can only be removed from the collection cabinet by authorized persons.

### [ Product information ]

All Wertheim standing safes in grade I, II and III can be equipped with a drop-in mechanism LBE150. According to the requested insurance class (resistance class burglary protection VSÖ-VVO) and the capacity of bags, the right safe can be chosen. Please note, that deposit safes are certified according to security class VSÖ – all other certifications expire due to the opening of the drop-in mechanism.

### [ Example deposit safe AM25RE ]

Security class	burglary protection according to EN1143-1, VSÖ: Class EN 1
Hinge	DIN right – model designation R option: DIN left
Door opening angle	180°
Body	double-walled, filled with high resistant barrier material
Door structure	triple-walled, filled with high resistant barrier material, internal boltwork protected by sheets of hardened steel to give extra anti-drill resistance
Locking mechanism	three-way moving boltwork with large steel bolts, protected by additional emergency re-lockers, continuous fixed full height bolt on the hinge side
Anchoring	prepared for floor and rear wall anchoring anchoring bolts and shields are supplied option: additional anchoring holes (customer specifies position)
Alarm connection	VdS-certified cable channels to allow connection to a burglar alarm system
Colour	inside and outside RAL 7037 dusty grey option: special colour according to RAL
Lock	model designation E – electronic lock VdS class 2, M-locks EM3520 option: other lock models (primary lock or possible secondary locks)
Equipment	it is recommended to install no internal equipment in deposit safes
Accessories	option: certified steel plinth to raise the level of the safe, fire protection door rebate seals, alarm switch set, interior lighting
Drop-in position	front and center option: on the back, on the back protruding, other options upon request
Maximum volume	subject to bag filling, position of drop-in equipment etc.

### [ Drop-in equipment LBE150 ]

Construction	massive steel structure with security blocking system
Weight	appr. 28 kg
Position	front, back, back protruding or upon request
Colour	inside and outside RAL 7037 dusty grey (always ident with safe colour) option: special colour according to RAL
Lock	cylinder lock with 5 keys option: further keys upon request
Drop-in goods	flexible envelopes max. DIN A4, max. 15 mm thick or cassettes with max. size 240 x 180 x 60 mm
Accessories	option: zipp-bag, cassette



Fig. Zipp-bag