



Fig. Swing-in door safe BWP1902, double-doored E-Lock La Gard Combogard PRO, 48 deposit boxes with mechanical magnetic lock

**Outside dimensions** 

h x w x d (mm)

1864 x 1416 x 688

Model

BWP1902K / BWP1902E





EN1143-1 Burglary protection



Grade II



Grade II



Class EN 2



4102 (light fire protection)



Domestic insurable up to EUR 100.000



Commercial insurable up to EUR 50.000

## [ Swing-in door safes ]

[ Type BWP ]

BWP series safes are fitted with swing-in doors. They are ideal for facilities (e.g. deposit boxes) where doors remain open during working hours and doors do not hinder. This safe does not have to be anchored.

#### [ Product information ]

Hinge double-doored

Door opening swing-in doors – upon opening, the doors slide into the side of the safe, leaving

the area in front of the safe completely free – several safes can be positioned

next to each other in a row, without open doors interfering each other.

Body triple-walled,

filled with armoured, high resistant barrier material

Door structure triple-walled, with armoured, high resistant barrier material, internal boltwork

protected by sheets of hardened steel to give extra anti-drill resistance

Locking mechanism three-way moving boltwork with large steel bolts protected by additional emer-

gency re-lockers, continuous fixed full height bolt on the hinge side

Anchoring fitted for floor anchoring

option: additional anchoring holes (customer specifies position)

Alarm connection VdS-certified cable channels to allow connection to a burglar alarm system

Colour inside and outside RAL 7037 dusty grey

option: special colour according to RAL

Lock model designation K – double-bit lock VdS class 1, Cawi 2 keys (95 mm)

model designation E — electronic lock VdS class 2, M-locks EM3520 option: other lock models (primary lock or possible secondary lock)


Equipment option: shelf, inside locker, drawer, pull-out shelf,

deposit boxes (upon request)

Accessories option: alarm switch set, interior lighting

### [ Equipment options ]





Please add 20 mm to the listed outside depth for mountings.

Volume

(1)

935

Weight

1250

(appr. kg)

Inside dimensions

h x w x d (mm)

1730 x 960 x 563

BWP1902 with shelves

shelves BWP1902 with deposit boxes





Fig. Swing-in door safe CWP0901, hinge right K-Lock Secu 2 keys (125 mm), 1 lockable drawer, 2 pull-out shelves





EN1143-1 Burglary protection



Grade III



Grade III



Class EN 3



Class III E (except K-Lock Secu)



4102 (light fire protection)



Domestic insurable



Commercial insurable up to EUR 100.000

# [ Swing-in door safes – desk safes ]

[ Type CWP ]

CWP series safes are fitted with swing-in doors and make working with the door open easy. The dimensions are chosen to enable an installation under a desk making it ideal for use in small areas.

### [ Product information ]

Hinge DIN right – model designation R (CWP0652, CWP0902 double-doored)

Door opening swing-in doors – upon opening, the doors slide into the side of the safe, leaving

the area in front of the safe completely free – several safes can be positioned next to each other in a row, without open doors interfering each other

Body triple-walled, reinforced, filled with armoured, high resistant barrier material

Door structure triple-walled, reinforced, filled with armoured, high resistant barrier material,

internal boltwork protected by sheets of hardened steel

to give extra anti-drill resistance

Locking mechanism three-way moving boltwork with large steel bolts protected by additional emer-

gency re-lockers, continuous fixed full height bolt on the hinge side

Anchoring fitted for floor anchoring

anchoring bolts and shields are supplied

option: additional anchoring holes (customer specifies position)

Alarm connection VdS-certified cable channels to allow connection to a burglar alarm system

Colour inside and outside RAL 7037 dusty grey

option: special colour according to RAL

Lock model designation K – double-bit lock VdS class 2, Secu 2 keys (125 mm)

model designation E – electronic lock VdS class 2, M-locks EM3520 option: other lock models (primary lock or possible secondary lock)

Equipment option: lockable drawer, pull-out shelf, cashier equipment Inkiess

lowest pull-out shelf with automatic push-out (100 mm)

Accessories option: alarm switch set, interior lighting

Option version multisafe certified in accordance with VdS 2450 grade III (SE105301)

	Model	Outside dimensions	Inside dimensions	Volume	Weight
		h x w x d (mm)	h x w x d (mm)	(1)	(appr. kg)
	CWP0651RK / CWP0651RE	648 x 850 x 754	486 x 514 x 590	147	515
	CWP0901RK / CWP0901RE	878 x 850 x 754	716 x 514 x 590	217	635
	CWP0652K / CWP0652E	648 x 1308 x 754	486 x 820 x 590	235	730
	CWP0902K / CWP0902E	878 x 1308 x 754	716 x 820 x 590	346	890

Please add 20 mm to the listed outside depth for mountings.



Fig. Cashier equipment Inkiess 880PL

### [ Cashier equipment Inkiess 880PL ]

Cashier equipment consists of: 8 boxes for single coins from 2 EURO to 1 EURO cent

8 banknote compartments and one role tray