

# Optional Accessories

Wertheim offers a wide range of accessories. Different customer requirements can be taken into account.

Please note that the accessory variants listed depend on the model. Please refer to the relevant model page for possible applications.



## VdS-Approved Steel Base

For optimum operability, the safe can be positioned on a VdS-recognised steel base. The plinth height can be selected from 65 mm to 800 mm. Steel plinths are available for the following safe models: AL, AN, AWS, BG, BM, BWS and CM.



## Fire Protection Door Rebate Seal

Safes that do not offer certified fire protection can be fitted with an optional fire protection door rebate seal.



## Interior Lighting

The aluminium-look LED light with integrated motion detector is battery-operated and rechargeable via micro USB. It is magnetic and can therefore be placed anywhere in the safe. Dimensions: 100 x 70 x 10.6 mm



## IAS Switch Set for Alarm Systems

Models with IAS connection preparation can be ordered with a switch set. VdS-approved alarm indicators and junction boxes (top side of safe door and inside of safe ceiling) enable correct monitoring of the door position and locking status. The switch set is installed by Wertheim, connection and fine adjustment are carried out on site.



**NOTE:** If a drawer/pull-out shelf is installed in the top position, a switch set is not possible for grade I, II and type CP safes. The connecting cable (door/car-cass) is designed here as a hanging loop.



## Additional Drill Holes

If further drill holes are required in addition to the prepared floor, rear wall or cable drill holes, these can be taken into account after notification of the position (side wall, rear wall, ceiling, floor) and technical inspection.



**NOTE:** When positioning special drill holes (especially in the side panel), possible interior fittings need to be taken into account. 1 piece of anchoring material is included as standard. Anchoring material is included in the scope of delivery. If additional anchors are required, this must be specified when ordering.