


AL Series



Safe AL15

Colour: Sand (body RAL 7021, door RAL 7030)
 Hinge: right
 Wittkopp Primor 2600 electronic lock

- Proven Wertheim quality
- Resistance grade I
- Light fire protection
- 4 standard colours to choose from

Privately insurable
 up to EUR 65.000

Commercial insurable
 up to EUR 20.000



EN1143-1
 Burglary protection



Grade I



Grade I



4102
 (light fire protection)



Class EN 1



Class I E

Standard Designs AL Series



Grey



Sand



Stone



Graphite

Product Information

Door Hinge

DIN right - standard
 optional: DIN left

Door Opening Angle

180°

Body

Multi-layered, highly resistant wall structure

Door Structure

Multi-layered, highly resistant wall structure, internal boltwork with partial drill protection

Locking

Three-way moving boltwork with large steel bolts, protected by an additional emergency locking mechanism, continuous profile on the hinge side

Anchoring

Prepared for floor and rear wall bolting, anchoring material included in the scope of delivery
 optional: additional holes (position according to customer requirements)

Cable Hole

2 x side wall (right and left)
 optional: additional holes (position according to customer requirements)

IAS Connection

VdS-certified pre-fitting for installation and connection to an intruder alarm system (IAS) from AL15

Colour

Available in four standard paint finishes
 Grey: body and door RAL 7037
 Sand: body RAL 7021, door RAL 7030
 Stone: body RAL 7021, door RAL 7035
 Graphite: body and door RAL 7021
 optional: paint finish according to RAL, also available in 2 colours (body, door)

Locks

Key lock VdS class 1, Wittkopp 2648, 2 keys (95 mm)
 Electronic lock VdS class 2, Wittkopp Primor 2600
 optional: other lock models

Interior

Adjustable shelf (from AL10)
 optional (from AL10): additional shelf, inside locker, drawer, pull-out shelf, optional (AL15): wooden interior ALZ007200

Accessories

Optional: VdS-approved steel plinth, fire protection door rebate seal, IAS switch set (from AL15), interior lighting

Modell Overview

AL Series



Model	AL03	AL05	AL10	AL15	AL20	AL25	AL30	AL35	AL40
Ext. dimensions h×w×d (mm) incl. hinges and handle	280×401×312	280×451×442	395×451×442	565×451×442	735×451×442	905×451×442	1075×451×442	1245×451×442	1415×451×442
Int. dimensions h×w×d (mm)	230×351×180	230×401×310	345×401×310	515×401×310	685×401×310	855×401×310	1025×401×310	1195×401×310	1365×401×310
Shelves Standard	1	1	1	1	1	2	2	3	3
Volume (l)	14	29	43	64	85	106	127	148	169
Weight* (appr. kg)	55	70	90	115	140	170	195	220	245

In addition to the indicated outer depth of the safe, a further 6 mm must be taken into account for the Primor electronic lock variant.

*The weight specifications correspond to the net weight (without packaging) including lock and the specified shelves.