

AN Series



Safe AN20

Colour: Grey
Hinge: right
Wittkopp 2648 key lock

- Proven Wertheim quality
- Resistance grade I
- Light fire protection

Privately insurable
up to EUR 65.000

Commercial insurable
up to EUR 20.000



EN1143-1
Burglary protection



Grade I



Grade I



4102
(light fire protection)



Class EN 1



Class I E

Product Information

Door Hinge

DIN right - standard
optional: DIN left

Door Opening Angle

180°

Body

Multi-layered, highly resistant wall structure

Door Structure

Multi-layered, highly resistant wall structure, internal boltwork with partial drill protection

Locking

Three-way moving boltwork with large steel bolts, protected by an additional emergency locking mechanism, continuous profile on the hinge side

Anchoring

Prepared for floor and rear wall bolting, anchoring material included in the scope of delivery
optional: additional holes (position according to customer requirements)

Cable Hole

2 x side wall (right and left)
optional: additional holes (position according to customer requirements)

IAS Connection

VdS-certified pre-fitting for installation and connection to an intruder alarm system (IAS)

Colour

Grey: RAL 7037
optional: paint finish according to RAL

Locks

Key lock VdS class 1, Wittkopp 2648, 2 keys (95 mm)
Electronic lock VdS class 2, Wittkopp Primor 2600
optional: other lock models (main locks or possible additional locks)

Interior

Adjustable shelf
optional: additional shelf, inside locker, drawer, pull-out shelf

Accessories

Optional: VdS-approved steel plinth, fire protection door rebate seal, IAS switch set, interior lighting



Model Overview

AN Series



Model	AN10	AN15	AN20	AN25	AN30	AN35	AN40
Ext. dimensions h×w×d (mm) incl. hinges and handle	395×545×442	565×545×442	735×545×442	905×545×442	1075×545×442	1245×545×442	1415×545×442
Int. dimensions h×w×d (mm)	345×495×310	515×495×310	685×495×310	855×495×310	1025×495×310	1195×495×310	1365×495×310
Shelves Standard	1	1	1	2	2	3	3
Volume (l)	53	79	105	131	157	183	209
Weight* (appr. kg)	100	130	160	190	220	250	280

In addition to the indicated outer depth of the safe, a further 6 mm must be taken into account for the Primor electronic lock variant.
*The weight specifications correspond to the net weight (without packaging) including lock and the specified shelves.