

AN Series



- Proven Wertheim quality
- Resistance grade I
- Light fire protection

Privately insurable up to EUR 65.000

EN1143-1

Commercial insurable

up to EUR 20.000

VdS

Grade I



Grade I



4102 (light fire protection)

Burglary protection



Class EN 1



Class I E

Product Information

Door Hinge

DIN right - standard optional: DIN left

Door Opening Angle

180°

Body

Multi-layered, highly resistant wall structure

Door Structure

Multi-layered, highly resistant wall construction, internal frame work space with partial drill protection

Locking

Driven on three sides by solid steel deadbolts via a boltwork with a base plate, protected by an additional emergency locking mechanism, continuous profile on the hinge side

Anchoring

Prepared for floor and rear wall bolting, Anchoring material included in the scope of delivery Optional: additional holes (position according to customer requirements)

Cable Drilling

2 x side panel (right and left, top rear panel) Optional: additional drill holes (position according to customer requirements)

IAS Connection

VdS-certified pre-fitting for installation and connection to an intruder alarm system (IAS)

Colour

Grey: RAL 7037 optional: paint finish according to RAL

Locks

Key lock VdS class 1, Wittkopp 2648, 2 keys (95 mm) Electronic lock VdS class 2, Wittkopp Primor 2600 Optional: other lock models (main locks or possible additional locks)

Interior

Optional: additional shelf, Interior safe, drawer, pull-out shelf

Accessories

Optional: VdS-approved steel plinth, fire protection door rebate seal, IAS switch set, interior lighting





Model Overview

AN series



Model	AN10	AN15	AN20	AN25	AN30	AN35	AN40
Ext. dimensions h×w×d (mm) incl. hinges and handle	395×545×442	565×545×442	735×545×442	905×545×442	1075×545×442	1245×545×442	1415×545×442
Int. dimensions h×w×d (mm)	345×495×310	515×495×310	685×495×310	855×495×310	1025×495×310	1195×495×310	1365×495×310
Shelves Standard	1	1	1	2	2	3	3
Volume (l)	53	79	105	131	157	183	209
Weight* (appr. kg)	100	130	160	190	220	250	280

In addition to the indicated outer depth of the safe, a further 6 mm must be taken into account for the Primor electric lock variant.

^{*}The weight specifications correspond to the net weight (without packaging) including lock and the specified shelves.