

AP Series



Safe AP15

Colour: Grey
Hinge: right
Wittkopp 2648 key lock

- Proven Wertheim quality
- Resistance grade I
- Certified fire protection

Privately insurable
up to EUR 65.000

Commercial insurable
up to EUR 20.000



EN1143-1
Burglary protection



Grade I



Grade I + LFS30
(AP10 - LFS60)



EN15659
Fire protection



Class EN 1

Product Information

Door Hinge

DIN right - standard
optional: DIN left

Door Opening Angle

180°

Body

Double-walled, filled with highly resistant filler and heat-absorbing materials

Door Structure

Triple-walled with double rebate, filled with highly resistant filler and heat-absorbing materials, internal boltwork with partial drill protection, door rebate with several fire and smoke protection seals

Locking

Three-way moving boltwork with large steel bolts, protected by an additional emergency locking mechanism, continuous profile on the hinge side

Anchoring

Prepared for floor and rear wall bolting, anchoring material included in the scope of delivery

Cable Hole

Door hinge side, rear wall bottom

IAS Connection

VdS-certified pre-fitting for installation and connection to an intruder alarm system (IAS)

Colour

Grey: RAL 7037
optional: paint finish according to RAL

Locks

Key lock VdS class 1,
Wittkopp 2648, 2 keys (145 mm)
Electronic lock VdS class 2,
Wittkopp Primor 2600
optional: other lock models (main locks or possible additional locks)

Interior

Adjustable shelf
optional: additional shelf, inside locker, drawer, pull-out shelf

Accessories

Optional: IAS switch set, interior lighting



Model Overview

AP Series



Model	AP10**	AP15	AP20	AP25	AP30	AP35	AP40
Ext. dimensions h×w×d (mm) incl. hinges and handle	474×605×522	629×605×522	799×605×522	969×605×522	1139×605×522	1309×605×522	1479×605×522
Int. dimensions h×w×d (mm)	360×495×310	515×495×310	685×495×310	855×495×310	1025×495×310	1195×495×310	1365×495×310
Shelves Standard	1	1	1	2	2	3	3
Volume (l)	55	79	105	131	157	183	209
Weight* (appr. kg)	180	220	260	305	350	390	435

In addition to the indicated outer depth of the safe, a further 6 mm must be taken into account for the Primor electronic lock variant.

*The weight specifications correspond to the net weight (without packaging) including lock and the specified shelves.

**AP10 - Fire protection LFS60