



- Proven Wertheim quality
- Resistance grade I
- Certified fire protection

Privately insurable

Commercial insurable

up to EUR 20.000

up to EUR 65.000

EN1143-1

Burglary protection

Grade I



Grade I + LFS30





Class EN 1

Product Information

Door Hinge

DIN right - standard optional: DIN left

Door Opening Angle

180°

Body

Double-walled design, filled with highly resistant filler and heatabsorbing materials

Door Structure

Designed with double rebate and triple walls, filled with highly resistant filler and heat-absorbing materials, internal transom space with partial drill protection, door rebate with several fire and smoke protection seals

Locking

Driven on three sides by solid steel deadbolts via a boltwork with a base plate protected by an additional emergency locking mechanism; continuous profile on the hinge side.

Anchoring

Prepared for floor and rear wall bolting connection, anchoring material included in the scope of delivery

Cable Drilling

Door hinge side, rear panel bottom

IAS Connection

VdS-certified pre-fitting for installation and connection to an intruder alarm system (IAS)

Colour

Grey: RAL 7037 optional: paint finish according to RAL

Locks

Key lock VdS class 1, Wittkopp 2648, 2 keys (145 mm) Electronic lock VdS class 2, Wittkopp Primor 2600 optional: other lock models (main locks or possible additional locks)

Interior

Optional: additional shelf, Interior safe, drawer, pull-out shelf

Accessories

Optional: IAS switch set, interior lighting





Model Overview

AP Series



Model	AP10"	AP15	AP20	AP25	AP30	AP35	AP40
Ext. dimensions h×w×d (mm) incl. hinges and handle	474×605×522	629×605×522	799×605×522	969×605×522	1139×605×522	1309×605×522	1479×605×522
Int. dimensions h×w×d (mm)	360×495×310	515×495×310	685×495×310	855×495×310	1025×495×310	1195×495×310	1365×495×310
Shelves Standard	1	1	1	2	2	3	3
Volume (l)	55	79	105	131	157	183	209
Weight* (appr. kg)	180	220	260	305	350	390	435

In addition to the indicated outer depth of the safe, a further 6 mm must be taken into account for the Primor electric lock variant.

^{*}The weight specifications correspond to the net weight (without packaging) including lock and the specified shelves.

^{**}AP10 - Fire protection LFS60