

BG Series



Safe BG20

Colour: Grey
hinge: right
Wittkopp 2648 key lock

- Proven Wertheim quality
- Resistance grade II
- Light fire protection

Privately insurable
up to EUR 100.000

Commercial insurable
up to EUR 50.000



EN1143-1
Burglary protection



Grade II



Grade II



DIN 4102
(light fire protection)



Class EN 2

Product Information

Door Hinge

DIN right - standard
optional: DIN left

Door Opening Angle

180°

Body

Double-walled design, filled with reinforced, highly resistant filler material

Door Structure

Three-walled design, filled with reinforced, highly resistant filler material, internal transom space with partially attached drill protection

Locking

Driven on three sides by solid steel bolts via a boltwork with a base plate, protected by an additional emergency locking mechanism, a continuous profile on the hinge side that engages behind it

Anchoring

Prepared for floor and rear wall bolting connection, anchoring material included in the scope of delivery
optional: additional holes (position according to customer requirements)

Cable Drilling

Door hinge side, top rear panel
optional: additional drill holes (position according to customer requirements)

IAS Connection

VdS-certified pre-fitting for installation and connection to an intruder alarm system (IAS) (from BG15)

Colour

Grey: RAL 7037
optional: paint finish according to RAL

Locks

Key lock VdS class 1, Wittkopp 2648, 2 keys (95 mm)
Electronic lock VdS class 2, Wittkopp Primor 2600
optional: other lock models (main locks or possible additional locks)

Interior

Adjustable shelf
optional: additional shelf, Interior safe, drawer, pull-out shelf
optional (BG15): Wooden fittings ALZ007200

Accessories

Optional: VdS-approved steel plinth, fire protection door rebate seal, IAS switch set (from BG15), interior lighting



Model Overview

BG Series



Model	BG10	BG15	BG20	BG25	BG30	BG35	BG40
Ext. dimensions h×w×d (mm) incl. hinges and handle	395×450×442	565×450×442	735×450×442	905×450×442	1075×450×442	1245×450×442	1415×450×442
Int. dimensions h×w×d (mm)	345×400×310	515×400×310	685×400×310	855×400×310	1025×400×310	1195×400×310	1365×400×310
Shelves Standard	1	1	1	2	2	3	3
Volume (l)	43	64	85	106	127	148	169
Weight* (appr. kg)	120	150	180	215	245	280	310

In addition to the indicated outer depth of the safe, a further 60 mm must be taken into account for fittings.
*The weight specifications correspond to the net weight (without packaging) including lock and the specified shelves.