

BG Series



Safe BG20

Colour: Grey
Hinge: right
Wittkopp 2648 key lock

- Proven Wertheim quality
- Resistance grade II
- Light fire protection

Privately insurable
up to EUR 100.000

Commercial insurable
up to EUR 50.000



EN1143-1
Burglary protection



Grade II



Grade II



4102
(light fire protection)



Class EN 2

Product Information

Door Hinge

DIN right - standard
optional: DIN left

Door Opening Angle

180°

Body

Double-walled, filled with armored
highly resistant filler material

Door Structure

Triple-walled, filled with armored
highly resistant filler material, internal
boltwork with partial drill protection

Locking

Three-way moving boltwork with
large steel bolts, protected by
an additional emergency locking
mechanism, continuous profile on the
hinge side

Anchoring

Prepared for floor and rear wall
bolting, anchoring material
included in the scope of delivery
optional: additional holes
(position according to customer
requirements)

Cable Hole

Door hinge side, rear wall top
optional: additional holes
(position according to customer
requirements)

IAS Connection

VdS-certified pre-fitting for
installation and connection to an
intruder alarm system (IAS) from BG15

Colour

Grey: RAL 7037
optional: paint finish according to RAL

Locks

Key lock VdS class 1,
Wittkopp 2648, 2 keys (95 mm)
Electronic lock VdS class 2,
Wittkopp Primor 2600
optional: other lock models (main
locks or possible additional locks)

Interior

Adjustable shelf
optional: additional shelf, inside locker,
drawer, pull-out shelf
optional (BG15):
Wooden interior ALZ007200

Accessories

Optional: VdS-approved steel plinth,
fire protection door rebate seal,
IAS switch set (from BG15),
interior lighting



Model Overview

BG Series



Model	BG10	BG15	BG20	BG25	BG30	BG35	BG40
Ext. dimensions h×w×d (mm) incl. hinges and handle	395×450×442	565×450×442	735×450×442	905×450×442	1075×450×442	1245×450×442	1415×450×442
Int. dimensions h×w×d (mm)	345×400×310	515×400×310	685×400×310	855×400×310	1025×400×310	1195×400×310	1365×400×310
Shelves Standard	1	1	1	2	2	3	3
Volume (l)	43	64	85	106	127	148	169
Weight* (appr. kg)	120	150	180	215	245	280	310

In addition to the indicated outer depth of the safe, a further 6 mm must be taken into account for the Primor electronic lock variant.
*The weight specifications correspond to the net weight (without packaging) including lock and the specified shelves.