

BM Series



Safe **BM35**

Colour: Grey
hinge: right
Wittkopp 2648 key lock

- Proven Wertheim quality
- Resistance grade II
- Light fire protection

Privately insurable
up to EUR 100.000

Commercial insurable
up to EUR 50.000



EN1143-1
Burglary protection



Grade II



Grade II



DIN 4102
(light fire protection)



Class EN 2

Product Information

Door Hinge

DIN right - standard
optional: DIN left

Door Opening Angle

180°

Body

Double-walled design, filled with reinforced, highly resistant filler material

Door Structure

Three-walled design, filled with reinforced, highly resistant filler material, internal transom space with partially attached drill protection

Locking

Driven on three sides by solid steel bolts via a boltwork with a base plate, protected by an additional emergency locking mechanism, a continuous profile on the hinge side that engages behind it

Anchoring

Prepared for floor and rear wall bolting connection, anchoring material included in the scope of delivery
optional: additional holes (position according to customer requirements)

Cable Drilling

Door hinge side, top rear panel
optional: additional drill holes (position according to customer requirements)

IAS Connection

VdS-certified pre-fitting for installation and connection to an intruder alarm system (IAS)

Colour

Grey: RAL 7037
optional: paint finish according to RAL

Locks

Key lock VdS Kl. 1,
Wittkopp 2648, 2 keys (95 mm)
Electronic lock VdS class 2,
Wittkopp Primor 2600
optional: other lock models (main locks or possible additional locks)

Interior

Adjustable shelf
optional: additional shelf,
interior safe, drawer, pull-out shelf

Accessories

Optional: VdS-approved steel plinth,
fire protection door rebate seal,
IAS switch set, interior lighting



Model Overview

BM Series



Model	BM10	BM15	BM20	BM25	BM30	BM35	BM40
Ext. dimensions h×w×d (mm) incl. hinges and handle	395×545×442	565×545×442	735×545×442	905×545×442	1075×545×442	1245×545×442	1415×545×442
Int. dimensions h×w×d (mm)	345×495×310	515×495×310	685×495×310	855×495×310	1025×495×310	1195×495×310	1365×495×310
Shelves Standard	1	1	1	2	2	3	3
Volume (l)	53	79	105	131	157	183	209
Weight* (appr. kg)	135	170	205	240	275	310	345

In addition to the indicated outer depth of the safe, a further 6 mm must be taken into account for the Primor electric lock variant.
*The weight specifications correspond to the net weight (without packaging) including lock and the specified shelves.