

# BP Series



**Safe BP15**

Colour: Grey  
Hinge: right  
Wittkopp 2648 key lock

- Proven Wertheim quality
- Resistance grade II
- Certified fire protection

**Privately insurable**  
up to EUR 100.000

**Commercial insurable**  
up to EUR 50.000



EN1143-1  
Burglary protection



Grade II



Grade II + LFS30  
(BP10/41 - LFS60)



EN15659  
Fire protection



Class EN 2

## Product Information

### Door Hinge

DIN right - standard  
optional: DIN left

### Door Opening Angle

180°

### Body

Double-walled, filled with armored highly resistant filler and heat-absorbing materials

### Door Structure

Triple-walled with double rebate, filled with armored highly resistant filler and heat-absorbing materials, internal boltwork with partial drill protection, door rebate with several fire and smoke protection seals

### Locking

Three-way moving boltwork with large steel bolts, protected by an additional emergency locking mechanism, continuous profile on the hinge side

### Anchoring

Prepared for floor and rear wall bolting, anchoring material included in the scope of delivery

### Cable Hole

Door hinge side, rear wall bottom

### IAS Connection

VdS-certified pre-fitting for installation and connection to an intruder alarm system (IAS)

### Colour

Grey: RAL 7037  
optional: paint finish according to RAL

### Locks

Key lock VdS class 1,  
Wittkopp 2648, 2 keys (145 mm)  
Electronic lock VdS class 2,  
Wittkopp Primor 2600  
optional: other lock models (main locks or possible additional locks)

### Interior

Adjustable shelf  
optional: additional shelf, inside locker, drawer, pull-out shelf

### Accessories

Optional: IAS switch set, interior lighting



## Model Overview

### BP Series



Model	BP10**	BP15	BP20	BP25	BP30	BP35	BP40	BP41**
<b>Ext. dimensions</b> h×w×d (mm) incl. hinges and handle	474×605×522	629×605×522	799×605×522	969×605×522	1139×605×522	1309×605×522	1479×605×522	1479×765×582
<b>Int. dimensions</b> h×w×d (mm)	360×495×310	515×495×310	685×495×310	855×495×310	1025×495×310	1195×495×310	1365×495×310	1365×655×370
<b>Shelves</b> Standard	1	1	1	2	2	3	3	3
<b>Volume</b> (l)	55	79	105	131	157	183	209	331
<b>Weight*</b> (appr. kg)	190	235	280	325	375	420	465	580

In addition to the indicated outer depth of the safe, a further 6 mm must be taken into account for the Primor electronic lock variant.

\*The weight specifications correspond to the net weight (without packaging) including lock and the specified shelves.

\*\*BP10/BP41 - Fire protection LFS60