

CM Series



Safe CM30

Colour: Grey
hinge: right
S&G key lock

- Proven Wertheim quality
- Resistance grade III
- Light fire protection

Privately insurable
up to EUR 200.000

Commercial insurable
up to EUR 100.000



EN1143-1
Burglary protection



Grade III



Grade III



4102
(light fire protection)



Class EN 3

Product Information

Door Hinge

DIN right - standard
optional: DIN left

Door Opening Angle

180°

Body

Double-walled, reinforced design,
filled with reinforced, highly resistant
filler material

Door Structure

Triple-walled, reinforced design,
with reinforced, highly resistant filler
material, internal transom space with
partially attached drill protection

Locking

Driven by solid steel bolts via a
boltwork, by means of additional
emergency locking mechanism
protected, one continuous profile on
the hinge side

Anchoring

Prepared for floor and rear wall
bolting, Anchoring material included
in the scope of delivery
optional: additional drill holes

Cable Drilling

Door hinge side, top rear panel
optional: additional drill holes
(position according to customer
DIN requirements)

IAS Connection

VdS-certified pre-fitting for installation
and connection to an intruder alarm
system (IAS)

Colour

Grey: RAL 7037
optional: paint finish according to RAL

Locks

Key lock VdS cl. 2, S&G, 2 keys
(140 mm)
Electronic lock VdS cl. 2, Wittkopp
Primor 2600
optional: other lock models (main
locks or possible additional locks)

Interior

Adjustable shelf
optional: additional shelf, interior safe,
drawer, pull-out shelf

Accessories

Optional: VdS-approved steel plinth,
fire protection door rebate seal,
IAS switch set, interior lighting



Model Overview

CM Series



Model	CM15	CM20	CM25	CM30	CM35	CM40
Ext. dimensions h×w×d (mm) incl. hinges and handle	595×575×495	765×575×495	935×575×495	1105×735×555	1275×735×555	1445×735×555
Int. dimensions h×w×d (mm)	515×495×310	685×495×310	855×495×310	1025×655×370	1195×655×370	1365×655×370
Shelves Standard	1	1	2	2	3	3
Volume (l)	79	105	131	248	290	331
Weight* (appr. kg)	280	335	390	565	635	705

In addition to the indicated outer depth of the safe, a further 6 mm must be taken into account for the Primor electric lock variant.
*The weight specifications correspond to the net weight (without packaging) including lock and the specified shelves.