

# CP Series




**Safe CP25**

Colour: Grey  
hinge: right  
S&G key lock

- Proven Wertheim quality
- Resistance grade III
- Certified fire protection

**Privately insurable**  
up to EUR 200.000


**Commercial insurable**  
up to EUR 100.000



EN1143-1  
Burglary protection




Grade III



Grade III + LFS30



EN15659  
Fire protection



Class EN 3

## Product Information

### Door Hinge

DIN right - standard  
optional: DIN left

### Door Opening Angle

180°

### Body

Double-walled, reinforced design, filled with reinforced, highly resistant filler and heat-absorbing materials

### Door Structure

With double rebate and triple-walled, reinforced design, filled with reinforced, highly resistant filler and heat-absorbing materials, inside transom space with partially attached drill protection, door rebate fitted with several fire and smoke protection seals

### Locking

Driven by solid steel bolts via a boltwork, by means of additional emergency locking mechanism protected, one continuous profile on the hinge side

### Anchoring

Prepared for floor and rear wall bolting, Anchoring material included in the scope of delivery contain

### Cable Drilling

Door hinge side, rear panel bottom

### IAS Connection

VdS-certified pre-fitting for installation and connection to an intruder alarm system (IAS)

### Colour

Grey: RAL 7037  
optional: paint finish according to RAL

### Locks

Key lock VdS cl. 2, S&G, 2 keys (140 mm)  
Electronic lock VdS cl. 2, Wittkopp Primor 2600  
optional: other lock models (main locks or possible additional locks)

### Interior

Adjustable shelf optional: additional shelf, interior safe, drawer, pull-out shelf

### Accessories

Optional: IAS switch set, interior lighting



## Model Overview

### CP Series



Model	CP15	CP20	CP25	CP30	CP35	CP40
<b>Ext. dimensions</b> h×w×d (mm) incl. hinges and handle	629×605×522	799×605×522	969×605×522	1139×605×522	1309×605×522	1479×605×522
<b>Int. dimensions</b> h×w×d (mm)	515×495×310	685×495×310	855×495×310	1025×495×310	1195×495×310	1365×495×310
<b>Shelves</b> Standard	1	1	2	2	3	3
<b>Volume</b> (l)	79	105	131	157	183	209
<b>Weight*</b> (appr. kg)	295	350	410	465	520	575

In addition to the indicated outer depth of the safe, a further 6 mm must be taken into account for the Primor electric lock variant.  
\*The weight specifications correspond to the net weight (without packaging) including lock and the specified shelves.