

DWSKB Series





Commercial insurable

up to EUR 250.000

Safe DWS1200KB Colour: Grev hinge: right 2 x S&G key lock

- Proven Wertheim quality
- Resistance grade IVKB
- Certified fire protection*
- Core drill protection

Privately insurable

by arrangement





Class EN 5

Grade IVKB + LFS30* LFS60* (optional)

Product Information

Door Hinge

DIN right - standard optional: DIN left Models 1902 and 1904 double-leaf

Door Opening Angle 180°

Body

Double-walled, reinforced design, with crown drilling protection, filled with reinforced, highly resistant filler material

Door Structure

Triple-walled, reinforced design, with crown drill protection, filled with reinforced, highly resistant filler, inside transom space with partially attached drill protection, door rebate fitted with several fire and smoke protection seals

Locking

Driven on 3 sides by solid steel bolts via a boltwork with a base, protected by a glass plate with additional emergency bolts, steel bolts welded on the hinge side to grip behind

Anchoring

Prepared for floor bolting, anchoring material included with models 0849 and 0850

Cable Drilling Door hinge side, ceiling and side panel

IAS Connection

VdS-certified pre-fitting for installation and connection to an intruder alarm system (IAS)

Colour

Grey: RAL 7037 optional: paint finish according to RAL

Locks

Safes from grade IV must be equipped with at least 2 locks, lock combinations (locks from VdS class 2) freely selectable

Interior

Adjustable shelf optional: additional shelf, inner safe optional models 0850KB-1901KB: drawer, pull-out shelf

Accessories

Optional: IAS switch set, interior lighting, certified fire protection LFS60* demountable version from model 1000 - assembly on site



*except models 0849KB, 1902KB and 1904KB KB = crown drill protection

Fire protection*



Model Overview

DWSKB Series



Model	DWS0849KB	DWS0850KB	DWS1000KB	DWS1200KB	DWS1600KB	DWS1901KB	DWS1903KB/1902KB**	DWS1904KB**
Ext. dimensions h×w×d (mm) incl. hinges	848×645×565	848×810×725	1003×810×725	1193×810×725	1538×810×725	1883×810×725	1883×1110×725	1883×1415×725
Int. dimensions h×w×d (mm)	695×495×320	695×660×480	850×660×480	1040×660×480	1385×660×480	1730×660×480	1730×960×480	1730×1265×480
Shelves Standard	1	1	2	2	3	4	4	4
Volume (l)	110	220	269	329	439	548	797	1050
Weight* (appr. kg)	635	875	1030	1150	1405	1680	2090/2130	2550

In addition to the indicated outer depth of the safe, a further 60 mm must be taken into account for fittings.

*The weight specifications correspond to the net weight (without packaging) including lock and the specified shelves. **Models 1902KB and 1904KB in double-leaf design